




**Europäisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**

PCT/EP2004 / 006405



Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03014353.1

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1 (a) OR (b)

BEST AVAILABLE COPY



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

PCT/EP2004 / 006405

Anmeldung Nr:

Application no.: 03014353.1

Demande no:

Anmeldetag:

Date of filing: 26.06.03

Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Sony Ericsson Mobile Communications AB

221 88 Lund

SUEDE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:

(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.

If no title is shown please refer to the description.

Si aucun titre n'est indiqué se référer à la description.)

Switch dome device

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)
revendiquée(s)

Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

H01H/

Am Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL
PT RO SE SI SK TR LI

SWITCH DOME DEVICE

Technical Field of the Invention

The present invention relates to a switch dome device
5 for operating functions in an electronic equipment.

Description of Related Art

To meet the increased demand from mobile phone and
smart phone users or the like for more advanced functions,
10 vendors offer mobile phones with more advanced input/output
devices such as larger displays, joysticks and rocker keys
to operate for example extensive entertainment functions.
State of the art miniature joysticks and rocker keys offer,
however, a limited number of activation directions, not
15 sufficient for playing games or executing other graphic
intensive functions.

A prior art rocker key device 1 is shown in a
schematic exploded top view in FIG 2A. The rocker key
device has a rocker key 2, a select button 3, switch domes
20 4, all of which are mounted on a support structure 5, such
as a PCB, for arrangement in for example a mobile phone.
With further reference to FIG 2B, an exploded bottom view
of the rocker key device 1 in FIG 2A is illustrated. The
rocker key 2 is provided with actuator bosses 6 integrated
25 in the rocker key 2 or in a supporting rubber for actuating
the switch domes 4, when the rocker key 2 is pushed by a
user.

FIG 3A illustrates an arrangement of the switch domes
4 in a four directional arrangement forming a part of a
30 rocker key device. The actuating directions are illustrated
by the arrows 7. As mentioned above, new functions and
applications require more actuating directions to be
operated properly.

One prior art arrangement to provide eight selectable
35 directions is extended from the four directional
arrangement shown in FIG 3A. Four switch domes 4 are used,

wherein one single switch dome is actuated for each of the four directions, i.e 0/90/180/270°, as shown in FIG 3A, and four additional directions 45/135/225/315°, as shown by the arrows 7 in FIG 3B. The positions of the switch domes 4 and the directions are related to the vertical orientation of the drawing sheets, which corresponds to the normal operation of a mobile phone provided with a rocker key device.

A problem associated with this design is that the user has to press two domes at the same time for the four additional directions 45/135/225/315°, which is almost impossible. There will be a time interval were only one dome is pressed, causing an initial unwanted selection of one of the first four directions 0/90/180/270°. This problem might be overcome by a software delay, long enough to secure that only the intended direction is properly selected. Since the response time has to match the slowest user, the phone appears slow for most users which is annoying. This is particularly noticeable when playing games on the phone.

Another problem with this arrangement is that the tilting angle and the actuation force of the joystick or rocker key is not the same for the 0/90/180/270° directions and the 45/135/225/315° directions.

Another prior art arrangement providing eight selectable directions is based on eight switch domes positioned on 0/45/90/135/180/225/270/315°, as shown in FIG 4A. Similarly to the four switch dome arrangement, a single switch dome is actuated at a time to select one of the eight directions.

A side view of a rocker key device 1 comprising eight switch domes is shown in FIG 4B. The distance from the actuator boss 6 of adjacent domes to the centre 8' of rotation is about 70% of the distance from the boss of the targeted dome to the centre 8' of rotation. The same ratio

applies for the vertical stroke. Hence, there is a potential risk that one of the domes adjacent to the intended dome is accidentally pressed. Without being precautions, this would result in an incorrect selection of two directions simultaneously. This can be compensated for by software that make the phone ignoring the input of more than one pressed dome at the same time. These cases will confuse and irritate the user of the phone. Intuitively, the user will press the key harder, but still without response from the phone. Even if the adjacent domes are not closing contact, the actuator, i.e the key and boss, will at least partially compress them. This will lead to a poor tactile feedback for the user.

15 **Summary of the Invention**

It is an object of the invention to overcome the problems of the prior art arrangements.

This object is achieved by a switch dome device for operating functions in an electronic equipment, wherein the device comprises a set of switch domes mounted in a circular pattern on a support structure. The switch dome device is characterized in that outputs of adjacent switch domes are operatively connected to inputs of a common AND circuit.

25 According to one aspect of the invention the switch domes are equally distributed around the circular pattern with the same distance to the centre of the circular pattern.

30 According to a more specific aspect of the invention the set of switch domes comprises eight switch domes.

A more specific object of the invention is to provide an improved input device for operating functions in an electronic equipment.

35 This object is achieved by an input device, comprising a switch dome device according to the invention

and a switch dome actuator for actuating switch domes of the switch dome device.

According to one aspect of the input device, the actuator is a rocker key provided with actuator bosses for
5 actuating the switch domes.

Another object of the invention is to use the inventive switch dome in a communication equipment for improved operation of for example applications and functions in the equipment.

10 This object is achieved by using the inventive input device in a portable communication equipment. The portable communication equipment may be a mobile radio terminal.

One advantage of the present invention is that a software response delay associated with the switch dome
15 activation is unnecessary. Also, the tilt angle and actuation forces are identical for all directions, and the tactile feedback is better.

It should be emphasized that the term "comprises/ comprising" when used in this specification is taken to
20 specify the presence of stated features, integers, steps or components but does not preclude the presence or addition of one or more other features, integers, steps, components or groups thereof.

25 Brief Description of the Drawings

In order to explain the invention in more detail and the advantages and features of the invention a preferred embodiment will be described in detail below, reference being made to the accompanying drawings, in which

30 FIG 1 shows a mobile radio terminal including an input device according to the invention;

FIG 2A is a schematic exploded top view of a prior art rocker key device,

FIG 2B is a schematic exploded bottom view of the
35 rocker key device in FIG 2A,

FIG 3A illustrates a schematic top view of four switch domes arranged in four selectable directions of operation,

5 FIG 3B illustrates a schematic arrangement of the switch domes in FIG 3A with four additional directions of operation to be selected,

FIG 4A illustrates a schematic arrangement of eight individually selectable switch domes providing eight selectable directions of operation,

10 FIG 4B shows a schematic side view of a rocker key device comprising the arrangement of FIG 4A,

FIG 5A illustrates a schematic arrangement of eight switch domes providing eight selectable directions of operation according to the invention, and

15 FIG 5B shows a schematic side view of a rocker key device according to the invention comprising the arrangement of FIG 5A.

Detailed Description of Embodiments

20 A first embodiment of an input device 1 to operate different applications such as playing games or executing other graphic intensive functions including extensive entertainment functions of an electronic equipment is shown in FIG 1.

25 The term electronic equipment includes portable radio communication equipment. The term portable radio communication equipment, which herein after is referred to as a mobile radio terminal, includes all equipment such as mobile phones, pagers, communicators, i.e. electronic
30 organizers, smartphones or the like.

Further, in the following description, numerous specific details are provided in detail in order to give a more thorough description of the present invention. However, it will be obvious for those skilled in the art
35 that the present invention may be implemented without these

specific details. Some well-known features are not described in detail so as not to make the present invention unclear.

In this embodiment, the input device is, but is not limited to, a rocker key device 1 mounted in a mobile radio terminal 10 and operatively connected to circuits therein. The rocker key device 1 comprises a rocker key 2 and a select button 3 for selection or activation of different functions etc of the mobile radio terminal 10. The input device of the invention is however not limited by the select button 3, but can operate without it. Further, the mobile radio terminal has, but is not limited to, additional details intended for the normal operation of a mobile radio terminal. In this embodiment the mobile radio terminal has a display 11, a microphone 12, a keypad 13, a speaker 14, an integrated antenna (not shown), and a radio transceiver (not shown), etc, all of which are operatively connected to circuits in the mobile radio terminal. All these additional details are however not necessary for the operation of the invention, but are provided for illustration purposes of elements of a mobile radio terminal, in which the invention is used.

The rocker key device is shown in further detail in FIGS 2A and 2B. The rocker key device 1 comprises the rocker key 2, the select button 3, switch domes 4, all of which are mounted in a support structure 5, such as a PCB, for arrangement in for example the mobile radio terminal 10 in FIG 1. An exploded bottom view of the rocker key device 1 in FIG 2A is illustrated in FIG 2B. The rocker key 2 is provided with actuator bosses 6 integrated in the key 2 or in a supporting rubber for actuating the switch domes 4, when the rocker key is pushed by a user.

FIGS 3A, 3B, 4A, and 4B disclose prior art arrangements.

FIG 5A illustrates a schematic arrangement of a set of eight switch domes 4 forming a switch dome device providing eight selectable directions 7 of operation, according to the invention. The eight selectable directions are based on the eight switch domes 4, equally distributed around a circular pattern on the support structure 5, with the same distance to the centre 8 of the circular pattern. The switch domes are positioned on 22,5/67,5/112,5/157,5/202,5/247,5/292,5/337,5° around the circular pattern and with respect to the orientation of the display of the mobile radio terminal 10 held in a vertical position for normal operation by a user. The invention is however not limited to the given positions of the domes and directions of actuation, but they can be rotated with a maintained intermediate distance between the domes. The individual switch domes and their functionality are well known to the skilled person in the art and are not described in further detail herein.

According to the invention, outputs of adjacent switch domes 4 are operatively connected to inputs of a common AND-circuit 9, as schematically illustrated in FIG 5A. The AND-circuit 9 is preferably implemented as, but is not limited to, an AND-gate, the logical operation of which is well known. The output of the AND circuit 1 is connected to other circuits on the PCB of the mobile radio terminal. For example, when a user intends to move a cursor in a particular direction, or in another way control an application or game, on the display 11 of the mobile radio terminal, the user actuates the rocker key device 1. The rocker key 2 is pressed on a location, preferably near the circumference of the upper side of the rocker key 2, to actuate a pair of switch domes 4 in a particular direction of the eight selectable directions 7. Each of the pressed switch domes 4 generates an output signal. If the user actuates two switch domes, whose outputs are connected to

inputs of the same AND-circuit 9, an output signal is generated from the AND-circuit 9. The output signal from the AND-circuit 9 is received by the circuits on the PCB for further control of the a cursor in a particular direction, or in another way control an application or game, on the display 11 of the mobile radio terminal. As is apparent from FIGs 5A and 5B, the tilt angle and actuation forces are identical for all directions.

The distance from the actuator boss 6 of adjacent domes 4 to the centre of rotation 8' is about 40% of the distance from the boss 6 of the targeted dome 4 to the centre of rotation 8'. The same ratio applies for the vertical stroke. Thus, the stroke of the actuator on the third dome is only 40% of that of the intended two domes to be pressed. Hence, the risk of accidentally hitting an adjacent third dome is very small. Even in case of a third dome being pressed, the "correct" domes will be pressed first and software in the phone can easily ignore the third contact.

Due to the AND-circuit 9, no response will be given if only one dome 4 is pressed. The intuitive user reaction of pressing a little harder will give the desired result. Further, the tactile feedback is better because the adjacent domes are hardly touched.

Hence, the present invention provides an input device and switch dome device for operating functions in an electronic equipment. However, the present disclosure of the embodiment described is to be considered as exemplification of the invention and it is not intended to limit the invention to the specific embodiment.

For example, in an alternative embodiment of the invention the input device is a joystick. In this alternative embodiment the domes are fitted in a plastic support structure, making contact with inmolded leads which also from the terminals of the component with which it is

mounted on the PCB. The number of switch domes can also vary between alternative embodiments, preferably eight or more are used. However, for less complex applications fewer than eight domes might be used.

CLAIMS

1. A switch dome device for operating functions in an electronic equipment (10), said device comprising a set of switch domes (4) mounted in a circular pattern on a support structure (5), characterized in that outputs of adjacent switch domes (4) are operatively connected to inputs of a common AND circuit (9).

2. A switch dome device according to claim 1, wherein said switch domes (4) are equally distributed around said circular pattern with the same distance to the centre (8) of said circular pattern.

3. A switch dome device according to claim 1 or 2, wherein said set of switch domes comprises eight switch domes (4).

4. An input device (1) for operating functions in an electronic equipment (10), comprising a switch dome device and a switch dome actuator (2) for actuating switch domes (4), characterized in that said switch dome device is a switch dome device according to any of the claims 1-3.

5. An input device according to claim 4, wherein said actuator (1) is a rocker key provided with actuator bosses (6) for actuating said switch domes (4).

6. An input device according to claim 4, wherein said actuator (1) is a joystick.

7. An electronic equipment, characterized by an input device (1) according to any of the claims 4-6.

8. An electronic equipment according to claim 7, wherein the switch domes (4) are positioned on the support

structure (5) on 22,5/67,5/112,5/157,5/
202,5/247,5/292,5/337,5° positions around the circular
pattern with respect to the orientation of a display (11)
of the electronic equipment held in a position for normal
5 operation by a user.

9. An electronic equipment according to claim 7 or 8,
wherein the electronic equipment is a mobile radio terminal
(10).

10

ABSTRACT

A switch dome device for operating functions in an electronic equipment (10), wherein the device comprises a set of switch domes (4) mounted in a circular pattern on a support structure (5), and outputs of adjacent switch domes (4) are operatively connected to inputs of a common AND circuit (9).

To be published together with Fig. 5B.

1/5




FIG. 1




FIG. 2A
Prior art




FIG. 2B
Prior art




FIG. 3A
Prior art




FIG. 3B
Prior art




FIG. 4A
Prior art




FIG. 4B
Prior art




FIG. 5A




FIG. 5B

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.